

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/050022 A1

(51) International Patent Classification⁷: **F04B 53/12**

(21) International Application Number:
PCT/US2004/038130

(22) International Filing Date:
15 November 2004 (15.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/519,887 14 November 2003 (14.11.2003) US

(71) Applicant (*for all designated States except US*): APPRO TEC USA [US/US]; 2435 Polk Street, San Francisco, CA 94109 (US).

(72) Inventors: FISHER, Martin, J.; San Francisco (US). CARLSON, Lawrence, E.; Boulder, CO (US). TAR-BELL, Ben; East Palo Alto, CA (US). KAPLAN,


Jonathan, I.; Palo Alto, CA (US). YOM-TOV, Opher, Doron; San Francisco, CA (US). ADLER, Ari, T.; San Francisco, CA (US). KURJAN, Christine, M.; Mountain View, CA (US). LISTER, Robert, Ian; Doronfield, GB (GB). BANERJEE, Shilajett; Belmont, CA (US). SWALEH, Mohammed; Nairobi, Kenya (KE). SPYBEY, Alan, C; P.O Box 454 Village Market, Nairobi, Kenya 00621 (KE). MUSA, Abdilkadir, Mohammed; Tanzania (KE).

(74) Agents: SAMUEL, Richard, I. et al.; Goodwin Procter LLP, 103 Eisenhower Parkway, Roseland, NJ 07068 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,

[Continued on next page]

(54) Title: DEEP WELL IRRIGATION PUMP



(57) Abstract: Provided herein are exemplary embodiments of an efficient pump apparatus. In one embodiment the pump apparatus comprises a piston assembly loosely disposed within a cylinder. The piston assembly includes a driving cable connecting a top leaky piston and a bottom leaky piston having a check valve connected thereto. The cylinder includes an outlet pipe at an upper portion thereof and a check valve located at a lower end of the cylinder. The pistons move in the cylinder at a velocity relative to the conduit such that as the pistons move along the cylinder they create a substantial tortuous leak path forming a hydrodynamic seal between the pistons and the cylinder.

WO 2005/050022 A1



PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.